



■ Overview

The RS-ES-400-28GSX is a 10G uplink managed Ethernet fiber switch independently developed by Rubisec.

It has 8*10/100/1000Base-T ports and 24*100/1000Base-X SFP ports and 4*1/10G SFP+ fiber slot ports. Each port can support wire-speed forwarding.

The RS-ES-400-28GSX has L2+ full network management function, supports IPV4/IPV6 management, static and dynamic route full line rate forwarding, complete security protection mechanism, complete ACL/QoS policy and rich VLAN functions, and is easy to manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP(<50ms) and ITU-T G.8032) ERPS(<20ms) to improve link backup and network reliability.

When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as port traffic control, VLAN division, and SNMP through the Web network management mode.

It satisfies high-density network application environment and is suitable for medium, large-scale scenes such as hotel, campus, park, shopping mall, scenic spot, hospital, bank to form an economical, efficient and reliable communication network.

Models	RS-ES-400-28GSX
Interface Characteristics	
Console Port	1*Console RS232 port
Fixed Port	8*10/100/1000Base-T ports 24*100/1000Base-X SFP ports 4*1/10G SFP+ fiber slot ports
Ethernet Port	10/100/1000Base-T(X) ports supports auto-sensing, full/ half duplex MDI/ MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meters) 100BASE-TX: Cat5 or later UTP(≤100 meters) 1000BASE-T: Cat5e or later UTP(≤100 meters)
Optical Fiber Port	1/10G SFP+ optical fiber port, default no include optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)
Optical Cable / Distance	Multi-mode: 850nm / 0~500M(1.25G), 0~300M(10G), Single-mode: 1310nm / 0~ 40KM, 1550nm / 0~120KM.
Chipset Parameters	
Network Management Type	L2+
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX, IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X, IEEE802.3ae 10GBase-SR/LR, IEEE802.3x
Forwarding Mode	Store and Forward (Full Wire Speed)
Switching Capacity	144Gbps (Non-blocking)
Forwarding Rate@64byte	107.14Mpps
MAC	32K
Jumbo Frame	9.6K
LED Indicators	Power: PWR (Yellow), System: SYS(Yellow), Network: Link (Yellow), Fiber port: L/A (Green)
Reset Switch	Yes, press and hold the switch for 10 seconds and release it to restore the factory settings

Power Supply

Total PWR / Input Voltage

60W (AC100-240V)

Power Consumption

Standby<20W,
Full Load<45W

Power Supply

Built-in power supply, AC 100~240V 50-60Hz 1.0A

Physical Parameters

Operation TEMP
/ Humidity

-20°C~+55°C, 5%~90% RH Non condensing

Storage TEMP
/ Humidity

-40°C~+80°C, 5%~95% RH Non condensing

Ingress Protection

IP30

Lighting Protection

4KV 8/20us

Dimension (L*W*H)

440*290*44.5mm

Net / Gross
Weight

<3.5kg / <4.3kg

Installation

Desktop, 19 inch 1U cabinet installation

Certification

CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS

Software Features

Interface	IEEE802.3X (Full-duplex) Port temperature protection setting No connection port automatic sleep Port green Ethernet Energy-saving setting Broadcast storm control based on port speed SFP+ optical port DDMI real-time digital diagnosis The speed limit of the message flow in the access port, minimum particle size is 64Kbps.
Layer 3 Features	L2+ Network Management The device supports Layer 2 Plus (L2+) network management features. It supports the ARP protocol with a maximum capacity of 1024 ARP entries. The device supports IPv4 and IPv6 static routing and default routing, with a maximum of 128 routing entries. Layer 3 routing and forwarding are supported, enabling communication between different network segments and different VLANs.
VLAN	Voice VLAN, QinQ configuration, IEEE802.1q VLAN based on MAC, VLAN based on the protocol 4K VLAN based on port, Port configuration of Access, Trunk, Hybrid
Port Aggregation	802.3ad LACP dynamic aggregation, Static aggregation; Max. 18 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d), RSTP (IEEE802.1w), MSTP (IEEE802.1s)
Industrial Ring Network Protocol	Support ERPS ring network, ring network self-healing time is less than 20ms, ITU-T G.8032; Max. 250 Rings; Max. 250 devices per ring.
Multicast	MLD Snooping v1/v2, Multicast VLAN IGMP Snooping v1/v2, Max 1024 multicast groups, Fast log out
Port Mirroring	Bidirectional traffic mirroring for basic ports
QoS	Flow-based Rate Limiting Flow-based Packet Filtering 8*Output queues of each port 802.1p/DSCP priority mapping Diff-Serv QoS, Priority Mark/Remark Queue Scheduling Algorithm (SP, WRR, SP+WRR)
ACL	Port-based Issuing ACL, ACL based on port and VLAN L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.
Security	IP-MAC-VLAN-Port binding ARP inspection, Anti-DoS attack AAA & RADIUS, MAC learning limit Mac black holes, IP source protection IEEE802.1X & MAC address authentication Broadcast storm control, Backup for host datum SSH 2.0, SSL, Port isolation, ARP message speed limit User hierarchical management and password protection
DHCP	DHCP Client, DHCP Snooping, DHCP Server, DHCP relay
Management	CPU instant utilization status view Console/AUX Modem/Telnet/SSH2.0 CLI One-key recovery, Cable Diagnose, LLDP Web Management (HTTPS), NTP, System work log, Ping Test Rubisec NMS- Smart Network Management System Platform (LLDP+SNMP) Download & Management on FTP, TFTP, Xmodem, SFTP, SNMP V1/V2C/V3
System	Category 5 Ethernet network cable Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network

Packing List	Content	Qty	Unit
Packing List	36-port 10G uplink managed L3 Ethernet fiber switch	1	SET
	RJ45-DB9 Line	1	PC
	AC Power Cable	1	PC
	Mounting Kits (Hanging Ear)	1	SET
	User Guide	1	PC
	Warranty Card	1	PC

Model	Description
Order Information	
RS-ES-400-28GSX	L3 managed Ethernet aggregation /core fiber switch with 8*10/100/1000Base-T ports and 24*100/1000Base-X SFP ports and 4*1/10G SFP+ fiber ports. Support 1U/19 inch rack installation.

<https://rubisec.com/>
Visit our website or contact your local Rubisec representative for more information.

Email: info@rubisec.com
Call us at: +372 5838 16 45
Head Office: Harju maakond, Kesklinna linnaosa, Viru väljak 2, 10111, Tallinn, Estonia
© 2026 Rubisec Corporation. All rights reserved.